AUTODOC CLUB

How to change spark plugs on **MERCEDES-BENZ CLK Convertible (A209)** – replacement guide

SIMILAR VIDEO TUTORIAL



This video shows the replacement procedure of a similar car part on another vehicle


Important!

This replacement procedure can be used for:
MERCEDES-BENZ CLK Convertible (A209) CLK 240 (209.461), MERCEDES-BENZ CLK Convertible (A209) CLK 320 (209.465), MERCEDES-BENZ CLK Convertible (A209) CLK 500 (209.475)

The steps may slightly vary depending on the car design.

This tutorial was created based on the replacement procedure for a similar car part on: MERCEDES-BENZ B-Class (W245) B 170 (245.232) MERCEDES-BENZ B-Class (W245) B 150 (245.231) MERCEDES-BENZ B-Class (W245) B 170 NGT (245.233) MERCEDES-BENZ B-Class (W245) B 160 (245.231) MERCEDES-BENZ B-Class (W245) B 180 (245.232)

REPLACEMENT: SPARK PLUGS – MERCEDES-BENZ CLK CONVERTIBLE (A209). TOOLS YOU NEED:



- High-temperature anti-seize lubricant
- Spark plug socket # 16
- Ratchet wrench
- Torque wrench
- Round-nose pliers
- Fender cover


Buy tools

Replacement: spark plugs – MERCEDES-BENZ CLK Convertible (A209).
AUTODOC experts recommend:

- The replacement procedure is the same for all spark plugs.
- All work should be done with the engine stopped.

REPLACEMENT: SPARK PLUGS – MERCEDES-BENZ CLK CONVERTIBLE (A209). RECOMMENDED SEQUENCE OF STEPS:


1. Open the hood.
2. Use a fender protection cover to prevent damaging paintwork and plastic parts of the car.
3. Remove the spark plug wire connectors from the spark plug wells. Use round-nose pliers.



Replacement: spark plugs – MERCEDES-BENZ CLK Convertible (A209).
Professionals recommend:

- Be careful to avoid damaging spark plug wires.
- Remember the sequence of the spark plug wires connectors.


4 Clean dirt, dust and debris from inside the spark plug wells.




5 Unscrew the spark plugs. Use the spark plug socket #16. Use a ratchet wrench.



6 Take out the spark plugs.



7 Apply a thin layer of a special high temperature anti-seize lubricant to the threads of the new spark plugs.




8

Install the new spark plugs into their mounting seats.



9

Screw new spark plugs and tighten them. Use the spark plug socket #16. Use a torque wrench. Tighten it to 27 nm torque.



Replacement: spark plugs – MERCEDES-BENZ CLK Convertible (A209). AUTODOC recommends:

- Don't tighten the plugs with excessive force. Exceeding tightening torque can damage the thread connection.
- Be careful when working with a spark plug wrench. Its skewing can cause damage to the threaded connection.

10

Install the spark plug wire connectors into the spark plug wells. Make sure you hear a click indicating that it is locked in place.



AUTODOC recommends:

- Replacement: spark plugs – MERCEDES-BENZ CLK Convertible (A209). Follow the installation steps.

11 Run the engine for a few minutes. This is necessary in order to make sure that the component operates properly.

12 Shut off the engine.

13 Remove the fender protection cover.

14 Close the hood.

WELL DONE!

VIEW MORE TUTORIALS

AUTODOC — TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE

DISCLAIMER:

The document contains only general recommendations that may be useful for you when you perform repair or replacement work. AUTODOC shall not be liable for any loss, injury, damage of property occurring in the repair or replacement process due to incorrect use or misinterpretation of the provided information.

AUTODOC shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for information purposes only and cannot replace advice from specialists.

AUTODOC shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AUTODOC strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.